

Sterilisation Table



12

- CAPACITY 60 LITERS
- BUILT-IN OSMOTIC SYSTEM
- DOUBLE VACUUM PUMP
- DOUBLE MOTOR-OPERATED LOCKING SYSTEM
- INTEGRATED USB STORAGE DEVICE
- ON BOARD PRINTER
- QUIKSTEAM PATENTED TECHNOLOGY
- ADDITIONAL DRYING OPTION
- « START DELAY » OPTION
- B/S/N-CLASS CYCLES INCLUDED

WEIGHT	Solids wrapped: 12 kg Porous: 6 kg
---------------	---------------------------------------

TECHNICAL DATA

VETASSURE B60		VETASSURE B60 SI		
fractionated				TYPE OF VACUUM
-		✔		INTEGRATED STEAM GENERATOR
Bowie&Dick/Hellix/Vacuum				TEST PROGRAMS
				BUILT-IN PRINTER
				MTS MEMORY TEST SYSTEM
				CONNECTION TO DATA LOGGER
		✔		INTERNAL USB DATA LOGGER
				WATER QUALITY SENSOR
				INTEGRATED WATER PURIFICATION SYSTEM
135 kg		138 kg		WEIGHT
655Wx850Dx755H mm				OVERALL MEASURES (WITHOUT CABINET)
ø350x622 mm				CHAMBER SIZE
nr. 4 aluminium trays: 2 trays 310Wx550Dx25H mm 2 trays 220Wx550Dx25H mm				TRAY SIZES
230 V ± 10% (1 phase)	400 V ± 10% (3 phases)			SUPPLY VOLTAGE
50-60 Hz				MAINS FREQUENCY
11 Amp	13 Amp per phase			RATED POWER